

# ATEM 4 M/E Constellation 4K



ATEM 4 M/E Constellation 4K is a massive 4 M/E Ultra HD live production switcher. It features 40 standards converted 12G-SDI inputs, 24 12G-SDI aux outputs, 4 DVEs, 16 ATEM Advanced Chroma Keyers, 4 media players, 4 independent Ultra HD multiviews, 2 SuperSource processors and more. You even get built in talkback and a professional 156 channel Fairlight audio mixer with EQ and dynamics!

**\$8,995**

## Connections

### Total Video Inputs

40

### Total Video Outputs

28

### Total Aux Outputs

24

### SDI Rates

1.5G, 3G, 6G, 12G.

### Total Audio Inputs

2 x balanced 1/4 inch Jack,  
1 x 32 stereo channel BNC MADI in,  
1 x 5 pin XLR Talkback.

### Total Audio Outputs

2 x balanced 1/4 inch Jack,  
2 x 32 stereo channel BNC MADI out,  
1 x 5 pin XLR Talkback.

### Timecode Connections

None

### Reference Input

Tri-Sync or Black Burst.

### Video Input Re-Sync

On all 40 inputs.

### Frame Rate and Format Converters

On all 40 inputs.

### SDI Video Inputs

40 x 10-bit 720p, 1080i, 1080p, 2160p.

### SDI Audio Inputs

2 Ch embedded audio on all SDI  
inputs.

### Extra Audio Inputs

1 x 5 pin XLR Talkback.

### SDI Video Outputs

28 x 10-bit 720p, 1080i, 1080p, 2160p.

### SDI Audio Outputs

2 Ch embedded into SDI output on all  
outputs.

### Extra Audio Outputs

1 x 5 pin XLR Talkback.

### SDI Program Outputs

Any of the 24 SDI outputs.

### Down Converted SDI Program Output

None

### SDI Preview Outputs

Any of the 24 SDI outputs.

### SDI Multi View Outputs

4

### HDMI Multi View Outputs

None

### Webcam Output

1 x USB-C supporting 720p or 1080p  
at PGM frame rate.

### Remote

RJ12 supports RS-422.

### Control Panel Connection

Ethernet supports 10/100/1000  
BaseT. Allows direct connection  
between panel and chassis, or  
via network.

### Internal Timecode Generator

Yes

### Talkback


RJ45 for 3rd party talkback systems.

## Tally Output

Added via ethernet connection to Blackmagic Design GPI and Tally Interface product. (Not included).

## Computer Interface

1 x USB-C port.



## Standards

### SD Video Standards

None

### HD Video Standards

720p50, 720p59.94, 720p60  
1080i50, 1080i59.94, 1080i60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60.

### Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30, 2160p50,  
2160p59.94, 2160p60.

### SDI Compliance

SMPTE 292M, SMPTE 296M, SMPTE  
424M, SMPTE 425M level A and B,  
SMPTE 2081-1, SMPTE 2081-10,  
SMPTE 2082-1 and SMPTE 2082-10,  
SMPTE 2082-12.

### Video Sampling

4:2:2

### Color Precision

10-bit.

### Color Space

REC 709, REC 2020.

### SDI Auto Switching

Automatically detects between 1.5G-SDI, level A and level B 3G-SDI, 6G-SDI and 12G-SDI.

---

## Product Specifics

### Upstream Keyers

16

### Downstream Keyers

4

### Advanced Chroma Keyers

16

### SuperSource

2

### Talkback Support

Yes

### Mix Minus Support

Yes

### Linear/Luma Keyers

21

### Transition Keyer (Stinger/DVE)

4 Stinger, 4 DVE.

### Total Number of Layers

28

### Pattern Generators

21

### Color Generators

2

### DVEs

4

### Control Panel

Front fascia emergency switching, software or optional hardware panel.

### Routable Windows

64

### Tally

Red for program and green for preview indication.

### Windows Source Labels

Yes

---

## Multi View Monitoring

### Multi View Monitoring

4 x 16 Multi View pattern options for up to 64 total views.

### Multi View Video Standard

Select HD or Ultra HD.

---

## Media Player

### Media Players

4

### Media Player Clip Length in 720 HD

3200 frames.

### Media Pool Video File Format

TGA Sequence.

### Channels

Fill and key for each media player.

### Media Player Clip Length in 1080 HD

1600 frames.

### Media Pool Audio File Format

WAV, MP3 and AIFF.

### Media Pool Still Image Capacity

64

### Media Player Clip Length in Ultra HD

400 frames.

### Media Pool Clip Capacity

4

### Media Pool Still Image Format

PNG, TGA, BMP, GIF, JPEG and TIFF.

---

## Display

### Interface

Minimum monitor resolution of 1366 x 768.

---

## Front panel

Built in HD LCD monitor for video, 42 LED buttons for setup and emergency switching, 8 source buttons, 4 transition buttons, 6 talkback selection and mix buttons, menu control knob and set button, front panel lock button.

---

## Processing

### Processing Delay

TBA

### Audio Mixer

156 Channel mixer  
Selectable On/Off/Audio-Follow-Video.  
Level and Peak metering.  
Master gain control.  
6 band parametric EQ, Dynamics including Expander, Gate, Compressor and Limiter.

### Down Conversion

TBA

---

## Software

### Control Panel Included

ATEM Software Control Panel included free for Mac 12.0 Monterey, Mac 13.0 Ventura or later and Windows 10 and 11.

### Software Updates

Using USB-C connection directly connected to Mac OS or Windows computers. Includes ATEM Setup Utility.

### Configuration

Set via ATEM Software Control Panel, excluding ATEM chassis IP address which is set via the ATEM Setup Utility connected via USB-C to chassis.

---

## Operating Systems



Mac 12.0 Monterey,  
Mac 13.0 Ventura or later.



Windows 10 and 11.

---

## Power Requirements

### Power Supply

2 x Internal 100 - 240 AC 50/60Hz.

### Power Usage

TBA

---

---

## Physical Specifications



---

## Physical Installation

### Physical Installation

2 rack units height.

---

## Environmental Specifications

### Operating Temperature

0° to 40° C (32° to 104° F)

### Storage Temperature

-20° to 60° C (-4° to 140° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

ATEM 4 M/E Constellation 4K

Welcome wallet with QR code for software download

---

## Warranty

12 Month Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2023, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller